

DC Standard Glasswashers

Introducing the new Standard Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



Standard Extra Range
SXG45
SXG50

Standard Range

SG35
SG40
SG45
SG50

- **Fast**
- **Economical**
- **Energy Efficient**
- **Space Saving**



Performance

Fast two minute wash cycle
ensures maximum productivity

New innovative wash pump
increases wash pressure improving results

Hydrodynamic basket slides
ensures optimum wash and rinse coverage

Rinse thermo-lock
delivers perfect rinse temperatures time after time

Dual loaded configuration
for faster start up and guaranteed wash temperatures **(SX Range only)**

Energy and Cost Savings

New innovative wash pump
saves 180W per hour

Double skinned cabinet
reduces noise and heat emissions whilst lowering running costs

Reduced water consumption
produces the optimum balance between water usage and hygiene

Improved rinse arms
increases initial response by 30% and rotation speed by 20%

Insulated boiler
lowers running costs and improves boiler recovery times **(SX Range only)**

Operation

Intuitive, simple controls
reduces user error and staff training

EasyClean filters
maintenance friendly filters protect critical components

Chemical auto-dosing
eliminates user intervention and prevents over or under dosing

Auto drain down (optional)
ensures rapid drain down with no need for user intervention

Integral water softener (optional)
softens water without the need for an external unit

'Welcome to a cleaner world'

Standard Range Glasswasher Specifications



	SG35	SG40	SG45	SG50
Cycle time	120 sec	120 sec	120 sec	120 sec
Baskets (x2)	350 x 350 mm	400 x 400 mm	450 x 450 mm	500 x 500 mm
Height	580 mm	630 mm	680 mm	680 mm
Width	420 mm	460 mm	515 mm	570 mm
Depth	470 mm	515 mm	555 mm	615 mm
Depth with door open	705 mm	795 mm	890 mm	950 mm
Load height	210 mm	260 mm	310 mm	320 mm
Drain height	120 mm	120 mm	120 mm	120 mm
Drain Ø	25 mm	25 mm	25 mm	25 mm
Wash tank	11 lts	14 lts	18 lts	20 lts
Boiler	2.8 lts	2.8 lts	2.8 lts	2.8 lts
Water usage	2.4 lts p/c	2.4 lts p/c	2.4 lts p/c	2.4 lts p/c
Wash element	1.6 kW	1.6 kW	1.6 kW	1.6 kW
Boiler element	2.8 kW	2.8 kW	2.8 kW	2.8 kW
Total load	3 kW	3 kW	3.1 kW	3.1 kW
Amps required	13 Amps	13 Amps	13 Amps	13 Amps
Detergent dosing	Yes	Yes	Yes	Yes
Rinse aid dosing	Yes	Yes	Yes	Yes
Water connection	3/4 BSP	3/4 BSP	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar	2-4 bar	2-4 bar
Drain pump	Optional	Optional	Optional	Optional
Internal softener*	Optional	Optional	Optional	Optional

Standard Extra Range Specifications



	SXG45	SXG50
Wash element	1.6 kW	1.6 kW
Boiler element	2.8 kW	2.8 kW
Total load	4.7 kW	4.7 kW
Amps required	20 Amps**	20 Amps**
All other data corresponds with	SG45	SG50

Where water hardness exceeds 100ppm a water softener is required.

*Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 125 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

**Can be configured to operate on either 13A or 3Ph+N upon request.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products Ltd.

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 1749 870055 f: +44 1749 870056 e: sales@dcproducts.co.uk www.dcproducts.co.uk

